

GRP5.12-SLV

Low Voltage Battery



Powered by Solar

KEY FEATURES

- Modular design, simplifies transport and installation.
- Excellent temperature performance, temperature of discharge @-20°C ~ +60°C.
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: maximum safety and life cycle.
- Capable of high-powered emergency-backup and Off-Grid function.

	GRP5.12-S2LV	GRP5.12-S3LV	GRP5.12-S4LV
Battery Parameter			
Battery Cell	LiFePO ₄		
Battery System Capacity	10.24kWh	15.36kWh	20.48kWh
Module Number	2	3	4
Nominal Capacity	200Ah	300Ah	400Ah
Depth of Discharge	80%		
Nominal Voltage	51.2V		
Voltage Range	43.2Vdc ~ 56.16Vdc		
Nominal Charge / Discharge Current	100A		
Dimension (W x H x D)	640 x 890 x 200 mm	640 x 1255 x 200 mm	640 x 1620 x 200 mm
Weight	119kg	167kg	215kg
Installation	Stacked		
Temperature of Charge	0 ~ 55°C		
Temperature of Discharge	-20°C ~ +60°C		
Protection Degree	IP65		
Communication Port	RS485, CAN		
Display	LED		
Operation Humidity	5% ~ 95%		
Max. Operating Altitude	2000m		
Cycle Life	6000@80% DOD, 25°C , 0.5C		
Certification	CE, IEC, UN38.3, MSDS		